


ALL-IN-ONE PRODUCT



ROTATING BLADE ALLOWS
UP TO **77,000** CLEAVES



ELECTRODE LIFE
UP TO **38,000**



BENEFITS AND FEATURES

Integrates 5 functions in one unit (stripping, cleaning, cleaving, splicing and protecting)

The fusion splicer with All-In-One system provides the best workability on the pole and limited work spaces

No scratches on fiber by thermal stripping

Compatible with Fusion Splice-On Connector (FSOC) in accordance with the industrial standard

Ideal for enterprise, data centers, broadband and FTTH network application

UPGRADE OPTION

VFL (Visual Fault Locator) utilizes a 650nm red laser to locate and visibly display any failure points throughout the cable

InGaAs Power Meter (indium, gallium, arsenide) detects the amount of power lost during transmission and can help correct potential errors



STRIPPING



CLEAVING



CLEANING



FUSION SPLICE-ON CONNECTORS



SPECIFICATIONS

KF4A

CATEGORY	DESCRIPTION
Fiber alignment	IPAAS Clad to Clad Alignment
Applicable type of fibres	0.25mm; 0.9m; 2.0mm; 3.0mm indoor cable
Fiber count	Single fiber
Applicable fiber dimensions	Cladding diameter: 125µm; Coating diameter: 150µm-3mm
Fiber setting and cleaved length	7mm to 16mm (0.28in to 0.63in)
Splicing modes	Splice mode: 300; Heat mode: 100
Typical splice loss	SM: 0.02dB; MM: 0.01dB; DS:0.04dB; NZDS:0.04dB
Return loss	>60dB
Splicing time	Typical 7 sec. with SM
Splice loss estimate	Available
Sleeve heating time	Typical 13 sec. with IS-60 mode, IS-60 sleeve
Applicable protection sleeve	40mm (2.4in); 60mm (1.5in) micro sleeve
Storage of splice result	Data: up to 5,000 ea; Image: up to 5,000 ea
Tension test	1.96N to 2.25N
Operating condition	Altitude: 0-5,000m above sea level; Temperature: 14°F~122°F; Humidity: 0-95%; Wind: 15m/s, non-condensing, dust proof, water proof, shock proof
Storage condition	Temperature: -40°C~80°C (-40°F~176°F); Humidity: 0-95%
Dimension	132(W) x 212(L) x 73(H)mm (without rubber protector)
Weight	1.5kg (including battery)
Viewing method and display	2 AXIS CMOS cameras with 109mm (4.3in) color LCD monitor
Fiber view and magnification	X/Y: 110X; Max: 220X
Power supply	Li-ion battery (DC 14.8V, 3400mAh); 100~240V AC charger
No. of splice cycles with battery	Typical 200 cycles
Electrode life	Up to 38,000 splices
Blade life	Up to 77,000 cleaves
Terminals	USB



STANDARD PACKAGE

CATEGORY	MODEL	Q'TY
Arc fusion splicer	SWIFT KF4A	1
Battery	KF-3400	1
Battery adapter	FY1701000	1
Instructions for use	-	1
Spare electrode	EI-24	1 pair
Transporting case	HC-11 (hard case)	1
Optical fiber holder	-	1 pair
Sleeve clamp	SC-01	1
Cooling tray	CT-01 (40mm(1.5in))	1
Allen wrench	LD-3300	1
USB cable	-	1
Hard brush	-	1
Soft brush	-	1
Tool box	-	1
Tweezer	-	1



OPTIONAL ACCESSORIES

CATEGORY	MODEL
Battery	KF-3400
Cleaver blade	BI-07
Electrode	EI-24
Transporting case	ILST-SS03(L) (soft case)
Work belt	WB-01
Sleeve	S09-C, S09, S30-C, S30
SOC connector	SC, LC, FC, ST
Manual stripper	CF-02
External power	DC 12V (available for car cigar jack)
Optical fiber holder	HS-250, HS-900, HS-2.5, HS-IN, KF4-SC/FC, KF4-ST-01, KF4-ILC, LS-900 (choose one)